




DEHUMIDIFIER DM

The **Dehumidifier DM** has been designed for the dehumidification of plastic granules.

Some thermoplastic resins have properties which mean they absorb moisture; before being processed, it's essential that these materials are dried first using dehumidifier air.



Technical data

Model Type	Capacity Lt	Turbine power Kw	Regeneration resistance power Watt	Boiler resistance Watt	Power - supply V - HZ
DM 45.1	45	0,4	2 x 3500	1 x 2200	380 - 50
DM 70.1	70	0,4	2 X 3500	1 X 2200	380 - 50
DM 100.1	100	0,9	2 X 3500	1 X 2800	380 - 50
DM 150.1	150	1,3	2 X 5000	1 X 5000	380 - 50
DM 200.1	200	1,3	2 X 5000	1 X 5000	380 - 50
DM 300.1	300	1,3	2 X 5000	1 X 5000	380 - 50
DM 400.1	400	1,7	2 X 5000	1 X 6500	380 - 50
DM 45.2	2 X 45	0,9	2 X 3500	2 X 2200	380 - 50
DM 70.2	2 X 70	0,9	2 X 3500	2 X 2200	380 - 50
DM 45.4	4 X 45	0,9	2 X 5000	4 X 2200	380 - 50
DM 70.4	4 X 70	1,3	2 X 5000	4 X 2200	380 - 50
DM 100.4	4 X 100	2,2	2 X 5000	4 X 2800	380 - 50